



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-11GHz
 VSWR: DC-11GHz... 1.15:1(Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI&PTFE

MicrowaveTown www.MicrowaveTown.com				DIRECTION OF VIEW		UNIT	TITLE		
						mm	N-TNC Adapter		
<small>PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN</small>				DRAWN	Min Zhou		DWG NO.		
				CHECKED	Shaoqing Du		Z345301Z01		
<small>UNLESS OTHERWISE SPECIFIED: 1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX 2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1° 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED ✓</small>				APPR.	Gang Cao		OUTLINE DRAWING		
				DO NOT SCALE DRAWING					
LTR	DESCRIPTION	DATE	APPR.						