



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-33GHz  
 VSWR: DC-33GHz... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI

<b>MicrowaveTown</b> www.MicrowaveTown.com		DIRECTION OF VIEW 	UNIT mm	TITLE 2.92mm-3.5mm Adapter	
<small>PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN</small>		DRAWN Min Zhou	DWG NO.		
		CHECKED Shaoqing Du	Z353601Z01		
		APPR. Gang Cao	OUTLINE DRAWING		
		<small>UNLESS OTHERWISE SPECIFIED 1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX 2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1° 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED ✓</small>			
LTR	DESCRIPTION	DATE	APPR.	DO NOT SCALE DRAWING	
				SIZE A4_h	
				SCALE 4:1	
				REV. V2.0	
				SHEET 1/1	

1

2

3

4

5

6

A

B

C

D

A

B

C

D

1

2

5

6