



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-33GHz  
 VSWR: DC-33GHz... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI

<b>MicrowaveTown</b> www.MicrowaveTown.com				DIRECTION OF VIEW 	UNIT mm	TITLE 1.85mm-3.5mm Adapter
<small>PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN</small>				DRAWN Shaoqing Du	DWG NO. Z353800Z01	
				CHECKED Haimin Zhang		
				APPR. Gang Cao		
				<small>UNLESS OTHERWISE SPECIFIED: 1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX 2. LINEARITY TOLERANCES ±0.1; ANGLE TOLERANCES ±1° 3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED</small>		
LTR	DESCRIPTION	DATE	APPR.	DO NOT SCALE DRAWING		SIZE A4_h
						SCALE: 4:1
						REV. V2.0
						SHEET 1/1

**OUTLINE DRAWING**