



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-40GHz  
 VSWR: DC-40GHz.... 1.25:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PTFE

**Microwavetown**  
 www.Microwavetown.com

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN



DIRECTION OF VIEW  
 UNIT  
 mm

TITLE  
**2.92mm Adapter**

DRAWN Min Zhou  
 CHECKED Shaoping Du  
 APPR. Gang Cao

DWG NO.  
**Z363600W01**

LTR	DESCRIPTION	DATE	APPR.

1. REMOVE ALL DIMENSIONS FROM ALL CORNERS, SHARP EDGES, AND RADIUS  
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1  
 3. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED  
 4. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED

DO NOT SCALE DRAWING

SIZE A4\_h SCALE: 1 REV. V2.0 SHEET 1/1

**OUTLINE DRAWING**

1 2

5 6