



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE

Microwavetown
 www.Microwavetown.com

PROPRIETARY INFORMATION, THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN

DIRECTION OF VIEW

 DRAWN: Min Zhou
 CHECKED: Shaoping Du
 APPR.: Gang Cao

UNIT
 mm

TITLE
2.92mm Adapter

DWG NO.
Z363611W01

OUTLINE DRAWING
 SIZE: A4_h SCALE: 1 REV: V2.0 SHEET 1/1

LTR	DESCRIPTION	DATE	APPR.

1. DRAW ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ARE AFTER PLATING, SURFACE FINISH: Ra
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISH: Ra

DO NOT SCALE DRAWING

1 2

5 6