



**Performance Features:**

Nominal Impedance: 50 $\Omega$   
 Frequency Range: DC-50GHz

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI&PTFE

**M** MicrowaveTown Company, LLC  
 1283 E. Route 66 Ave.  
 Glendora, CA 91741  
 Tel: (626)241-9635  
 Fax: (626)698-1638  
 www.microwavetown.com

DIRECTION OF VIEW	UNIT	TITLE
	mm	2.4mm Connector

<small>PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN</small>				DRAWN Shaoqing Du CHECKED Haimin Zhang APPR. Gang Cao	DWG NO. <b>D370P0503F06</b>		
<small>UNLESS OTHERWISE SPECIFIED:          1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX          2. LINEARITY TOLERANCES <math>\pm 0.1</math>; ANGLE TOLERANCES <math>\pm 1^\circ</math>          3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1          4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED <math>\checkmark</math></small>				DO NOT SCALE DRAWING	OUTLINE DRAWING		
LTR	DESCRIPTION	DATE	APPR.	SIZE A4_h	SCALE 4:1	REV. V2.0	SHEET 1/1