


Performance Features:	
Nominal Impedance: 50Ω	
Frequency Range: DC-33GHz	
VSWR: DC-33GHz... 1.15:1 (Max)	
Materials/Finishes:	
Housing: SU303F	
Polished & Passivated	
Center Contact: Beryllium Copper	
Gold Plated	
Insulators: PEI	

<div>MicrowaveTown</div> <div>www.MicrowaveTown.com</div>				<div>DIRECTION OF VIEW</div> <div></div>		<div>UNIT</div> <div>mm</div>		<div>TITLE</div> <div>2. 4mm-3. 5mm Adapter</div>					
<div>PROPRIETARY INFORMATION: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM MICROWAVETOWN</div>				<div>DRAWN</div>	Shaoqing Du		<div>DWG NO.</div> <div>Z353710Z01</div>						
				<div>CHECKED</div>	Haimin Zhang								
								<div>APPR.</div>	Gang Cao		<div>OUTLINE DRAWING</div>		
				<div>UNLESS OTHERWISE SPECIFIED</div> <div>1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX</div> <div>2. LINEARITY TOLERANCES ± 0.1, ANGLE TOLERANCES $\pm 1^{\circ}$</div> <div>3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1</div> <div>4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED ✓</div>									
LTR	DESCRIPTION	DATE	APPR.	DO NOT SCALE DRAWING				SIZE A4_h		SCALE4: 1			
										5		6	